

## DC Protection Box DCB-NF-1I-1000V-I16A-I-II-10

For use with high voltage DC strings up to 1000Vdc

- IP65
- Glass Reinforced Polyester Base
- Polycarbonate Lid
  - RAL 7032
  - Impact Resistant
  - Double Insulated Class II
  - Ambient Temperature range: -25°C / +40°C
  - Max Operating Voltage:
    1000V AC / 1500V DC
  - External Earth Stud
- This product is designed to provide individual string protection and external isolation for Solar PV strings.
- The enclosure is fitted with Original Staubli MC-4 Solar Connectors for ease of connection of input strings.
- The enclosure provides excellent protection against the elements and is UV stabilized
- Pre-wired internal switchgear improves the system installation time.
- Connectors are clearly marked to streamline installation

IN / I OUT DC PROTECTION BOX



## 1 IN / 1 OUT DC PROTECTION BOX

## **Technical Data**

Number of Inputs	1 string input
Number of Outputs	1 string output
Surge Protection Device	1000V DC Type I & II
Max current	16A
Max String Voltage -Voc	1000Vdc
String Connection	Staubli MC-4 set
IP Rating	IP 65
Enclosure Material	Glass Reinforced Polyester
Enclosure Color	RAL 7032
UV Stabilized	Yes
Additional Heat Dissipation	M12 ventilation plug
NRCS Regulatory Approval	Yes - components certified under NRCS
Enclosure size	231 x 238 x 118mm





245 Masjien Street Strijdom Park, Randburg www.segensolar.co.za