SMA Solar Technology AG | Sonnenallee 1 | 34266 Niestetal | Germany
Phone: +49 561 9522-0 | Fax: +49 561 9522-100 | Internet: www.SMA.de | E-mail: info@SMA.de
Amtsgericht (District court) Kassel HRB (registration number) 3972
Chairman of the Supervisory Board: Dr. Erik Ehrentraut
Managing Board: Ulrich Hadding, Dr.-Ing. Jürgen Reinert, Pierre-Pascal Urbon



Manufacturer's Declaration

Zero Feed-in Mode (Zero Export) for PV Systems

From firmware version 1.11.4.R, the Sunny Home Manager is equipped with a new feature that reduces feed-in of locally generated PV power to the utility grid to a minimum. This makes it possible to realize PV systems with almost 100% self-consumption.

In Zero Export mode, the Sunny Home Manager ensures that the PV power currently generated by the inverters always matches the current power consumption of the household. If an active load/appliance in the household is switched off, the grid feed-in of excess PV power will automatically be reduced to a value less of than 2% of nominal PV system power within a reaction time of 1.5 to 2.5 seconds.

This control characteristic is valid under the following conditions:

- 1. When the Sunny Home Manager 2.0 (HM-20) is installed at the grid-connection point via its integrated measuring device, the control of feed-in power is being carried out correctly.
- 2. An SMA Energy Meter must be installed at the grid-connection point in connection with the Sunny Home Manager Bluetooth (HM-BT-10).
- 3. All necessary installation measures are carried out and checked in accordance with the installation manual of the Sunny Home Manager.
- 4. Configuration of the active power limitation settings to 0% is done by a qualified technician.

Information:

- In case of Sunny Home Manager Bluetooth (HM-BT-10): If DO meters are used to measure the power level for grid feed-in and grid purchase at the grid-connection point, the Zero-Feed-in reaction time of will be prolonged due to the significantly slower output of measured values. The maximum permitted rate of measured value output is fixed at 1 value per 4 seconds. If measurement values are received in larger intervals, the PV inverters will permanently be set to an output power of 0 W AC.
- 2. S0 meters are not supported.
- 3. In terms of zero export, the operation of a Sunny Boy Smart Energy is not being supported. The use of other SMA inverters is possible as of firmware version 1.13.

Niestetal, 2017-04-12 SMA Solar Technology AG

loleun lung

ppa. Dr.-Ing. Johannes Kneip EVP Development Center