



Product Service

Attestation of Conformity

No. N8A 072092 0291 Rev. 06

Holder of Certificate: **Shanghai JA Solar Technology Co., Ltd.**
 No. 118, Lane 3111,
 West Huancheng Road
 Fengxian District
 201401 Shanghai
 PEOPLE'S REPUBLIC OF CHINA

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Poly-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 704061604126-19

Date, 2019-09-27 (Zhulin Zhang)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICATE ◆ ZERTIFIKAT ◆ CERTIFICATE



Product Service

Attestation of Conformity

No. N8A 072092 0291 Rev. 06

Model(s):

1500 V DC Maximum System voltage, Fire Safety Class C Modules:
 JAP6(K)-72-xxx/4BB/1500V, xxx= 310 to 330 in step of 5;
 JAP6(K)-60-xxx/4BB/1500V, xxx= 255 to 275 in step of 5;
 1500 V DC Maximum System voltage, Fire Safety Class A Modules:
 JAP72D00-xxx/SC,xxx= 310 to 340 in step of 5;
 JAP60D00-xxx/SC, xxx= 260 to 285 in step of 5;
 JAP72D00-xxx/PR, xxx= 330 to 345 in step of 5;
 JAP60D00-xxx/PR, xxx= 275 to 290 in step of 5;
 JAP72D09-xxx/SC, xxx= 330 to 345 in step of 5;
 JAP60D09-xxx/SC, xxx= 275 to 290 in step of 5;
 1000 V DC Maximum System voltage, Fire Safety Class C Modules:
 JAP6(K)-72-xxx/4BB, xxx= 310 to 330 in step of 5;
 JAP6(K)-60-xxx/4BB, xxx= 255 to 275 in step of 5;
 JAP72S02-xxx/SC, xxx= 310 to 345 in step of 5;
 JAP60S02-xxx/SC, xxx= 255 to 290 in step of 5;
 JAP72S02-xxx/PR, xxx= 330 to 345 in step of 5;
 JAP60S02-xxx/PR, xxx= 275 to 285 in step of 5;
 JAP72S08-xxx/SC, xxx =320 to 345, in step of 5;
 JAP60S08-xxx/SC, xxx =270 to 290, in step of 5;
 JAP72S08-xxx/PR, xxx =335 to 355, in step of 5;
 JAP60S08-xxx/PR, xxx =280 to 295, in step of 5;
 1000 V DC or 1500 V DC Maximum System voltage,
 Fire Safety Class C Modules:
 JAP72S01-xxx/SC, xxx= 310 to 345 in step of 5;
 JAP60S01-xxx/SC, xxx= 255 to 290 in step of 5;
 JAP72S01-xxx/PR, xxx= 330 to 345 in step of 5;
 JAP60S01-xxx/PR, xxx= 275 to 285 in step of 5;
 JAP72S03-xxx/SC, xxx =320 to 345, in step of 5;
 JAP60S03-xxx/SC, xxx =270 to 290, in step of 5;
 JAP72S03-xxx/PR, xxx =335 to 355, in step of 5;
 JAP60S03-xxx/PR, xxx =280 to 295, in step of 5;
 JAP72S09-xxx/SC, xxx= 320 to 345 in step of 5;
 JAP60S09-xxx/SC, xxx= 265 to 290 in step of 5;
 JAP72S10-xxx/SC, xxx= 335 to 350 in step of 5;
 JAP60S10-xxx/SC, xxx= 275 to 290 in step of 5;
 JAP72S01-xxx/MS, xxx= 325 to 340 in step of 5;
 JAP60S01-xxx/MS, xxx= 270 to 280 in step of 5;
 JAP72S03-xxx/MS, xxx= 320 to 345 in step of 5;
 JAP60S03-xxx/MS, xxx= 270 to 285 in step of 5
 xxx is standing for rated output power at STC

Parameters:

Construction: Framed or Frameless, with Junction box, Cable and Connectors.
 Test Laboratory: Yangzhou Opto-Electrical Products Testing Institute
 No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
 Safety Class: Class II
 Maximum System Voltage: 1500 or 1000 V DC
 Fire Safety Class: Class C or Class A according to UL790.

Tested according to:

EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

ZERTIFIKAT • CERTIFICATE • CERTIFICADO • CERTIFICAT