

KODAK Solar Battery Storage

L1-BMU-BASE

L1-BATT



L1

The L1 is the most recent released low voltage solar battery storage system. The newly designed system provides simplified connection to save valuable time for installers.

The stacking system provides flexible configurations from 7.10 kWh to 24.86 kWh capacity.

The indoor/outdoor compatible feature provides more possibilities of installation. Ideal for large home and small commercial application.

7.10~24.85 kWh
Flexible Mounting
Plug&Play
90% DOD



KODAK Solar Battery Storage

L1

SPECIFICATIONS

Battery Module	2	3	4	5	6	7
Nominal Capacity(kWh)	7.10	10.65	14.20	17.75	21.30	24.85
Voltage Range (Vdc)	45 - 54					
Dimension(W*D*H cm)	60*38*53	60*38*70	60*38*87	60*38*104	60*38*121	60*38*138
Weight(kg)	84	119	154	189	225	260
Depth of Discharge	90%	90%	90%	90%	90%	90%
(Recommend)	30	45	60	75	90	100
Current(A)(Continuous)	74	100	100	100	100	100
(Peak@15S)	110	110	110	110	110	110
Communication	CAN, RS485					
Protection Class	IP 55					
Working Temperature(°C)	0-50					
Storage Temperature(°C)	-20-60					
Humidity(%)	5 - 95					
Design Life	15 ⁺ Years(25°C)					
Authentication Level	IEC62619/CE/UN38.3					

