

## NH fuse-link 500V combi indicator M1GL 125

Article number: N1014605



(Illustration similar)

### Description

NH fuse-links with utilization category gG mostly with combi indicator and live gripping lugs according to IEC 60269 respectively DIN EN 60269-1 and DIN VDE 0636-2 with a rated voltage of AC500V.

### Features

<b>Type:</b>	M1gL125
<b>Utilization category:</b>	gG
<b>Rated voltage AC:</b>	500V
<b>Size:</b>	NH1
<b>Rated current:</b>	125A
<b>Indicator / Signalling:</b>	Combi indicator
<b>Pre-arcing Joule integral (at 4ms):</b>	51000A <sup>2</sup> s
<b>Operating Joule integral at U<sup>n</sup>:</b>	260000A <sup>2</sup> s
<b>Power dissipation at rated current:</b>	12.9W
<b>Packaging unit:</b>	3
<b>Rated breaking capacity AC:</b>	120kA
<b>Contact type:</b>	Blade contact
<b>Gripping lugs:</b>	live
<b>Approvals:</b>	<ul style="list-style-type: none"> <li>• EAC</li> <li>• VDE</li> </ul>

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 11.12.2020 / 10:30