

Attestation of Conformity

N8A 086470 0033 Rev. 00

Holder of Certificate:

Ningbo Ginlong Technologies Co., Ltd.

No.57 Jintong Road

Binhai Industrial Park, Xiangshan 315712 Ningbo, Zhejiang

PEOPLE'S REPUBLIC OF CHINA

Product:

Converter

Hybrid Inverter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.:

704091623701-00

Date.

2018-07-19

(Zhengdong Ma)

Dell Wa

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

N8A 086470 0033 Rev. 00

Model(s):

RHI-3K-48ES, RHI-3.6K-48ES, RHI-4.6K-48ES, RHI-5K-48ES.

Parameters:

PV inputs:	
Max. input voltage:	d.c. 600V
MPP voltage range:	d.c. 90-520V
Max. input current:	d.c. 2x11A
Isc PV (absolute maximum):	d.c. 2x17.2A
Battery:	
Battery type:	Li-ion
Battery voltage range:	d.c. 42-58V
Max. charge/discharge current:	d.c. 62.5A/62.5A
AC output (back-up):	
Rated output voltage/frequency:	a.c. 230V/50Hz
Rated output current:	a.c. 13A
Rated output power:	d.c. 3000W
AC-output (grid side):	
Rated output voltage/frequency:	a.c. 230V/50Hz
Max. apparent output power:	3300VA (RHI-3K-48ES) 4000VA (RHI-3.6K-48ES) 4600VA (RHI-4.6K-48ES) 5500VA (RHI-5K-48ES)
Max. output current:	a.c. 15.7A (RHI-3K-48ES) a.c. 17.3A (RHI-3.6K-48ES) a.c. 23A (RHI-4.6K-48ES) a.c. 23.9A (RHI-5K-48ES)
Displacement factor:	-0.81+0.8
AC-Input:	
Voltage range:	a.c. 180270V
Current (maximum continuous):	23.9A
Frequency range:	47-52Hz / 57-62Hz
Protection class:	
Degree of protection:	IP65
Overvoltage category:	II (DC), III (MAINS)
Ambient temperature:	-25°C+60°C

Tested according to: EN 62109-1:2010 EN 62109-2:2011

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

WILL NO